











UL 752

US Underwriter Laboratories Standard

Test and classification for Ballistic Resistant Materials

	Class Threat Level	Type of Weapon	Calibre	Ammunition	No of Shots	Min / Max FPS	(m) Test Range
	1	Hand Gun	9mm x 19	FMJ	3	1175 1293	4.6
	2	Hand Gun	.357 Magnum	JSP	3	1250 1375	4.6
	3	Hand Gun	.44 Magnum	LSW GC	3	1350 1485	4.6
	4	30.06 Rifle	30.06	LSP	1	2540 2794	4.6
	5	7.62 Rifle	7.62x51	LC/FMJ Military Ball	1	2750 3025	4.6
	6	9 mm Uzi	9mm x19	FMJ LC	5	1400 1540	4.6
	7	5.56 Rifle	5.56 x 45	FMJ LC	5	3080 3383	4.6
	8	7.62 Rifle	7.62 x 51	LC/FMJ Military Ball	5	2750 3025	4.6
	9	12 Gauge	Rifled Slug	Lead 28g	3	1585	4.6
	10	Shot Gun	00 buckshot	Lead 42g	3	1744	

Ammunition Legend:

FMJ	Full Metal Jacketed
JSP	Jacketed Soft Point
LWC GC	Semi Wadcutter Gas Checked
LSP	Lead Core Soft Point
LC	Lead Core

This information is provided as a simple reference guide and does not contain all the relevant testing criteria. Please contact Architectural Armour for more information about our Ballistic Resistant Products or the appropriate testing standards agency for a full detailed specification.