



The unit has to be supported at the inner side

From the outside, the front-opening counter will be pushed into the ready cut-out. Inside the unit has to be supported. All remaining jointings to the brickwork, resp. glass frame have to be sealed with mineral wool and silicone according to the fire-resistance requirements.

The drive is manually.

Although the unit is produced with greatest care, after long operation repairs might become necessary. Therefore it should be possible to pull out the unit to the outside.

Subject to alterations.

- surface: Alu, laquered: 143670
- surface: stainless steel: 143507

EI90 Front Opening Transaction Tray Without Speech

Part Numbers
EI90/630/501 Al Lacq
EI90/630/501 SS

REV	DESCRIPTION	DATE

 Architectural Armour +44(0)1981 257000 sales@architecturalarmour.com www.architecturalarmour.com	DRAWN	INITIALS	DWG. NO: .	FOR ILLUSTRATIVE PURPOSES ONLY. DO NOT SCALE FROM THIS DRAWING. ALL DIMENSIONS TO BE VERIFIED ON SITE. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM. THIS DRAWING/SPECIFICATION REMAINS THE COPYRIGHT OF ARCHITECTURAL ARMOUR AND MUST NOT BE COPIED IN ANY FORM WHATSOEVER WITHOUT PRIOR WRITTEN PERMISSION.
	APPV'D	.		
SCALE	1:10@A4	EI90 Front Opening Transaction Tray Without Speech		
WEIGHT	.	4 The Courtyard, Station Rd, Dullingham. CB9 9UP. UK		