UL 752

US Underwriter Laboratories Standard Test and classification for Ballistic Resistant Materials

	Class Threat Level	Type of Weapon	Calibre	Ammunition	No of Shots	Min / Max FPS	(m) _{Test} Range 4.6
	1	Hand Gun	9mm x 19	FMJ	3	1175 1293	4.6
	2	Hand Gun	.357 Magnum	JSP	3	1250 1375	4.6
	3	Hand Gun	.44 Magnum	LSW GC	3	1350 1485	4.6
	4	30.06 Rifle	30.06	LSP	1	2540 2794	4.6
7	5	7.62 Rifle	7.62x51	LC/FMJ Military Ball	1	2750 3025	4.6
	6	9 mm Uzi	9mm x19	FMJ LC	5	1400 1540	4.6
	7	5.56 Rifle	5.56 x 45	FMJ LC	5	3080 3383	4.6
-	8	7.62 Rifle	7.62 x 51	LC/FMJ Military Ball	5	2750 3025	4.6
	9	30.06 Rifle	30.06	SC FMJ (APM2)	1	2715 2987	4.6
	10	.50 Rifle	M2	FMJCJ Military Ball	1	2810 3091	4.6
	Shotgun	12 Guage	Rifled Slug	Lead 28g	3	1585 1744	4.6
	Shotgun	Shot Gun	00 buckshot	Lead 42g	3	1200 1320	4.6


Ammunition Legend:

FMJ Full Metal Jacketed JSP Jacketed Soft Point

LWC GC Semi Wadcutter Gas Checked

LSP Lead Core Soft Point

LC Lead Core



This information is provided as a simple reference guide and does not contain all the relevant testing criteria. Please contact Architectural Armour for more information about our Ballistic Resistant Products or the appropriate testing standards agency for a full detailed specification.

